

# LYNKED G3-PLC NODES



## CN-10 & CN-20

- Extend your network to devices in hard-to-reach areas
- Enable your device to communicate regardless of device type or manufacturer
- Synchronizes and leverages the LYNKED Gateway backbone
- Easily add and remove devices to nodes
- Suitable for commercial and residential use



## FEATURES

- ✓ G3-PLC Compliant (Power-Line Carrier)
- ✓ Mesh-enabled and compatible with all LYNKED gateways
- ✓ Two layers of forward error correction (FEC) for robust data communication in harsh channels
- ✓ Overcurrent and short-circuit protection
- ✓ OFDM-based PHY (BPSK, QPSK, 8PSK) makes efficient use of the spectrum
- ✓ Adaptive tone mapping for optimal bandwidth utilization

*Your Partner in Transformation*

# CN-10

## PULSE-2-PLC NODE



- Connect your pulse meters to a PLC network
- Supports all types of smart meter technologies
- Each node supports up to 3 pulse devices
- Minimum pulse duration: 10 ms
- Transmission media: common wire, double wire, or UTP
- Network encryption for data in motion (AES encryption)
- Support pulse CVV up to 12V DC (PPPN)
- Power: 120-240Vac

# CN-20

## RS485-2-PLC NODE



- Connect your RS-485 meters to a PLC network
- Supports two-wire and four-wire RS-485 communications (RS-422 capable)
- Transmission media: common wire, double wire, or UTP
- Network encryption for data in motion (AES encryption)
- Adjustable baud rate
- Power: 120-240Vac



[www.lynked.io](http://www.lynked.io)



[sales@lynked.io](mailto:sales@lynked.io)



+1 (888) 311 5577